

2019

OTR Rim and Wheel Weight Chart



RIMS

1-PIECE

RIM SIZE DIA. - WIDTH / FLANGE HT.	RECOMMENDED TIRE SIZE	AVERAGE RIM WEIGHT LBS (KG)	MAXIMUM RIM WEIGHT LBS (KG)
24-9.00GR / 1.5	13.00R24 TG	89.0 (40.4)	- (-)
	14.00R24 TG	89.0 (40.4)	- (-)
	16.00R24 TG	89.0 (40.4)	- (-)
25-12.00LR / 1.4	15.5R25	103.0 (46.7)	- (-)
25-13.00LR / 1.4	15.5R25	106.0 (48.1)	- (-)
	17.5R25	106.0 (48.1)	- (-)
25-14.00LR / 1.4	17.5R25	109.0 (49.4)	- (-)
56.5-20.0 / 1.25	27-56.5	1,124.5 (510.1)	1,211.0 (549.3)
56.5-22.00 / 1.25	30-56.5	1,163.5 (527.8)	1,263.0 (572.9)

RIM SIZE DIA. - WIDTH / FLANGE HT.	RECOMMENDED TIRE SIZE(S)	COMPONENT WEIGHTS						AVG. ASSEMBLY WT. LBS (KG)	MAX. ASSEMBLY WT. LBS (KG)
		AVG. RIM BASE WT. LBS (KG)	MAX. RIM BASE WT. LBS (KG)	AVG. SIDE RING WT. LBS (KG)	MAX SIDE RING WT. LBS (KG)	AVG. LOCK RING WT. LBS (KG)	MAX. LOCK RING WT. LBS (KG)		
24-8.00 / 1.4	10.00-24TG								
	12.00-24TG	57.3 (26.0)	- (-)	19.0 (8.6)	- (-)	5.3 (2.4)	- (-)	81.6 (37.0)	- (-)
	13.00-24TG								
	14.00-24TG								
24-10.00 / 1.7	13.00-24TG	99.7 (45.2)	- (-)	36.5 (16.6)	- (-)	5.3 (2.4)	- (-)	141.4 (64.1)	- (-)
	14.00-24TG	136.8 (62.1)	174.0 (78.9)	43.5 (19.7)	50.4 (22.9)	5.6 (2.6)	6.0 (2.7)	182.8 (82.9)	224.2 (101.7)
	16.00-24TG	99.7 (45.2)	- (-)	36.5 (16.6)	- (-)	5.3 (2.4)	- (-)	141.4 (64.1)	- (-)
24-10.00 / 1.7 (F)	13.00-24TG								
	14.00-24TG	99.9 (45.3)	- (-)	36.5 (16.6)	- (-)	5.3 (2.4)	- (-)	141.6 (64.2)	- (-)
	16.00-24TG								
25-10.00 / 1.5	14.00-25	101.6 (46.1)	- (-)	42.2 (19.1)	- (-)	5.4 (2.5)	- (-)	149.2 (67.7)	- (-)
25-12.00 / 1.3	15.5-25	77.7 (35.2)	95.1 (43.1)	35.3 (16.0)	- (-)	5.4 (2.5)	- (-)	118.4 (53.7)	135.8 (61.6)
25-14.00 / 1.5	17.5-25	103.3 (46.9)	128.3 (58.2)	42.2 (19.1)	- (-)	5.4 (2.5)	- (-)	151.0 (68.5)	175.9 (79.8)
25-17.00 / 1.7 (AL) Large Gutter	20.5-25	101.6 (46.1)	128.2 (58.1)	54.6 (24.8)	- (-)	5.4 (2.5)	- (-)	161.6 (73.3)	188.2 (85.4)
25-17.00 / 1.7 (VL) Small Gutter	20.5-25	75.0 (34.0)	- (-)	54.6 (24.8)	- (-)	5.4 (2.5)	- (-)	135.0 (61.2)	- (-)
25-17.00 / 2.0	20.5R25	300.0 (136.1)	- (-)	49.2 (22.3)	- (-)	7.2 (3.3)	- (-)	374.2 (169.8)	- (-)
25-19.5 / 2.5	23.5-25	327.3 (148.5)	- (-)	44.5 (20.2)	- (-)	12.2 (5.5)	- (-)	384.0 (174.2)	- (-)
25-22.00 / 3.0	26.5-25	404.6 (183.5)	- (-)	56.2 (25.5)	- (-)	12.2 (5.5)	- (-)	473.0 (214.5)	- (-)
25-25.00 / 3.5	29.5-25	458.5 (208.0)	- (-)	66.8 (30.3)	- (-)	12.2 (5.5)	- (-)	537.5 (243.8)	- (-)

RIMS

4-PIECE

RIM SIZE DIA. - WIDTH / FLANGE HT.	RECOMMENDED TIRE SIZE(S)	COMPONENT WEIGHTS								AVG. ASSEMBLY WT. LBS (KG)	MAX. ASSEMBLY WT. LBS (KG)
		AVG. RIM BASE WT. LBS (KG)	MAX. RIM BASE WT. LBS (KG)	AVG. SIDE RING WT. [X2 IF NO BEADSEAT BAND] LBS (KG)	MAX. SIDE RING WT. [X2 IF NO BEADSEAT BAND] LBS (KG)	AVG. BEADSEAT BAND WT. [IF ONLY ONE SIDE RING] LBS (KG)	MAX. BEADSEAT BAND WT. [IF ONLY ONE SIDE RING] LBS (KG)	AVG. LOCK RING WT. LBS (KG)	MAX. LOCK RING WT. LBS (KG)		
24-8.50 / 1.7	12.00R24	84.0 (38.1)	- (-)	20.0 (9.1)	- (-)	- (-)	- (-)	10.0 (4.5)	- (-)	134.0 (60.8)	- (-)
24-10.00 / 2.0	13.00-24	142.3 (64.5)	- (-)	26.5 (12.0)	- (-)	- (-)	- (-)	20.2 (9.2)	- (-)	215.5 (97.7)	- (-)
	14.00-24	54.0 (24.5)	- (-)	60.0 (27.2)	- (-)	68.0 (30.8)	- (-)	14.0 (6.4)	- (-)	196.0 (88.9)	- (-)
	14.00-24	109.7 (49.8)	148.0 (67.1)	37.2 (16.9)	60.0 (27.2)	- (-)	- (-)	14.7 (6.7)	20.2 (9.2)	198.8 (90.2)	215.5 (97.7)
24-11.25 / 2.375	16.00-24	73.3 (33.2)	- (-)	63.0 (28.6)	- (-)	68.0 (30.8)	- (-)	14.0 (6.4)	- (-)	218.3 (99.0)	- (-)
49-19.50 / 4.0	27.00-49	1,198.0 (543.4)	- (-)	293.0 (132.9)	- (-)	165.1 (74.9)	- (-)	29.8 (13.5)	- (-)	1,685.9 (764.7)	- (-)

RIMS

5-PIECE

RIM SIZE DIA. - WIDTH / FLANGE HT.	RECOMMENDED TIRE SIZE(S)	COMPONENT WEIGHTS								AVG. ASSEMBLY WT. LBS (KG)	MAX. ASSEMBLY WT. LBS (KG)
		AVG. RIM BASE WT. LBS (KG)	MAX. RIM BASE WT. LBS (KG)	AVG. BEADSEAT BAND WT. LBS (KG)	MAX. BEADSEAT BAND WT. LBS (KG)	AVG. SIDE RING WT. [X2] LBS (KG)	MAX. SIDE RING WT. [X2] LBS (KG)	AVG. LOCK RING WT. LBS (KG)	MAX. LOCK RING WT. LBS (KG)		
24-10.00 / 2.0	14.00R24	186.0 (84.4)	- (-)	35.0 (15.9)	- (-)	25.0 (11.3)	- (-)	4.0 (1.8)	- (-)	275.0 (124.7)	- (-)
25-10.00 / 1.5	14.00R25	143.5 (65.1)	177.0 (80.3)	44.0 (20.0)	54.0 (24.5)	22.0 (10.0)	- (-)	8.5 (3.9)	12.0 (5.4)	240.0 (108.9)	287.0 (130.2)
25-11.00 / 2.0	16.00R25	193.0 (87.5)	196.0 (88.9)	54.0 (24.5)	- (-)	28.0 (12.7)	- (-)	14.0 (6.4)	16.0 (7.3)	317.0 (143.8)	322.0 (146.1)
25-11.25 / 2.0	16.00-25	167.2 (75.8)	167.4 (75.9)	58.4 (26.5)	- (-)	28.1 (12.7)	- (-)	12.6 (5.7)	13.0 (5.9)	294.4 (133.5)	294.6 (133.6)
25-13.00 / 2.5	18.00R25	205.8 (93.4)	215.0 (97.5)	62.5 (28.3)	75.0 (34.0)	44.3 (20.1)	44.5 (20.2)	13.3 (6.0)	16.0 (7.3)	366.0 (166.0)	394.0 (178.7)
25-14.00 / 1.5	17.5R25	226.5 (102.7)	240.0 (108.9)	60.0 (27.2)	66.0 (29.9)	22.0 (10.0)	- (-)	14.0 (6.4)	16.0 (7.3)	344.5 (156.3)	366.0 (166.0)
25-15.00 / 3.0	21.00R25	250.2 (113.5)	298.0 (135.2)	66.5 (30.1)	75.0 (34.0)	59.1 (26.8)	62.0 (28.1)	13.3 (6.0)	16.0 (7.3)	446.2 (202.4)	500.0 (226.8)
25-17.00 / 2.0	20.5R25	281.9 (127.9)	316.0 (143.3)	59.9 (27.2)	68.0 (30.8)	28.1 (12.7)	- (-)	13.3 (6.0)	16.0 (7.3)	411.2 (186.5)	445.0 (201.8)
25-17.00 / 3.5	24.00-25	175.8 (79.7)	- (-)	58.4 (26.5)	- (-)	66.8 (30.3)	- (-)	12.2 (5.5)	- (-)	380.0 (172.4)	- (-)
25-19.00 / 2.5	23.5R25	326.0 (147.9)	- (-)	54.0 (24.5)	- (-)	44.0 (20.0)	- (-)	12.0 (5.4)	- (-)	480.0 (217.7)	- (-)
25-19.50 / 2.5	23.5R25	321.0 (145.6)	418.3 (189.7)	66.2 (30.0)	75.0 (34.0)	47.1 (21.4)	52.8 (23.9)	13.9 (6.3)	16.0 (7.3)	503.9 (228.6)	610.9 (277.1)
25-22.00 / 3.0	26.5R25	331.4 (150.3)	382.0 (173.3)	64.4 (29.2)	71.4 (32.4)	59.1 (26.8)	62.0 (28.1)	13.3 (6.0)	16.0 (7.3)	525.9 (238.6)	588.0 (266.7)
25-25.00 / 3.5	29.5R25	427.5 (193.9)	547.0 (248.1)	71.7 (32.5)	90.0 (40.8)	88.0 (39.9)	132.0 (59.9)	13.5 (6.1)	16.0 (7.3)	683.7 (310.1)	913.0 (414.1)
25-30.00 / 1.5	67x34-25	406.0 (184.2)	- (-)	56.0 (25.4)	- (-)	22.0 (10.0)	- (-)	12.0 (5.4)	- (-)	518.0 (235.0)	- (-)
29-17.00 / 3.5	24.00-29	311.4 (141.2)	- (-)	82.1 (37.2)	- (-)	77.0 (34.9)	- (-)	14.2 (6.4)	- (-)	561.7 (254.8)	- (-)

RIM SIZE DIA. - WIDTH / FLANGE HT.	RECOMMENDED TIRE SIZE(S)	COMPONENT WEIGHTS								AVG. ASSEMBLY WT. LBS (KG)	MAX. ASSEMBLY WT. LBS (KG)
		AVG. RIM BASE WT. LBS (KG)	MAX. RIM BASE WT. LBS (KG)	AVG. BEADSEAT BAND WT. LBS (KG)	MAX. BEADSEAT BAND WT. LBS (KG)	AVG. SIDE RING WT. [X2] LBS (KG)	MAX. SIDE RING WT. [X2] LBS (KG)	AVG. LOCK RING WT. LBS (KG)	MAX. LOCK RING WT. LBS (KG)		
29-22.00 / 3.0	26.5-29	376.5 (170.8)	- (-)	82.1 (37.2)	- (-)	63.7 (28.9)	- (-)	14.2 (6.4)	- (-)	600.2 (272.2)	- (-)
29-24.00 / 3.0	30/65-29	412.4 (187.1)	- (-)	82.1 (37.2)	- (-)	63.7 (28.9)	- (-)	14.2 (6.4)	- (-)	636.1 (288.5)	- (-)
29-24.00 / 3.5	26.5-29	400.0 (181.4)	- (-)	82.1 (37.2)	- (-)	77.0 (34.9)	- (-)	14.2 (6.4)	- (-)	650.3 (295.0)	- (-)
29-25.00 / 3.5	29.5R29	515.8 (233.9)	573.0 (259.9)	92.1 (41.8)	102.0 (46.3)	80.0 (36.3)	83.0 (37.6)	14.7 (6.7)	16.0 (7.3)	787.9 (357.4)	857.0 (388.7)
29-27.00 / 3.5	33.25R29	662.5 (300.5)	735.0 (333.4)	102.0 (46.3)	- (-)	83.0 (37.6)	- (-)	14.0 (6.4)	- (-)	944.5 (428.4)	1,017.0 (461.3)
33-13.00 / 2.5	18.00R33	390.9 (177.3)	545.0 (247.2)	115.6 (52.4)	147.6 (67.0)	71.2 (32.3)	100.0 (45.4)	19.5 (8.8)	22.8 (10.3)	655.1 (297.2)	797.0 (361.5)
33-15.00 / 3.0	21.00R33	513.0 (232.7)	- (-)	132.0 (59.9)	- (-)	133.0 (60.3)	- (-)	23.0 (10.4)	- (-)	934.0 (423.7)	- (-)
33-22.00 / 4.0	27.00-33	493.0 (223.6)	- (-)	111.8 (50.7)	- (-)	119.6 (54.2)	- (-)	16.2 (7.3)	- (-)	860.2 (390.2)	- (-)
33-28.00 / 3.5	35/65R33	802.7 (364.1)	935.0 (424.1)	120.0 (54.4)	138.0 (62.6)	114.5 (52.0)	148.0 (67.1)	17.7 (8.0)	21.0 (9.5)	1,167.0 (529.3)	1,390.0 (630.5)
33-28.00 / 4.0	33.5-33	538.4 (244.2)	- (-)	111.8 (50.7)	- (-)	119.6 (54.2)	- (-)	16.2 (7.3)	- (-)	905.6 (410.8)	- (-)
33-32.00 / 3.5	37.5R33	965.0 (437.7)	- (-)	117.0 (53.1)	- (-)	108.0 (49.0)	- (-)	21.0 (9.5)	- (-)	1,319.0 (598.3)	- (-)
33-32.00 / 4.5	37.5-33	588.3 (266.8)	- (-)	111.8 (50.7)	- (-)	139.4 (63.2)	- (-)	16.2 (7.3)	- (-)	995.1 (451.4)	- (-)
35-15.00 / 3.0	21.00R35	455.4 (206.6)	712.0 (323.0)	117.4 (53.3)	132.0 (59.9)	95.5 (43.3)	133.0 (60.3)	21.3 (9.6)	23.0 (10.4)	776.1 (352.0)	1,133.0 (513.9)
35-17.00 / 3.5	24.00R35	536.6 (243.4)	823.0 (373.3)	124.2 (56.3)	142.8 (64.8)	135.2 (61.3)	194.0 (88.0)	22.3 (10.1)	25.2 (11.4)	953.7 (432.6)	1,332.0 (604.2)
35-27.00 / 3.5	33.25R35	730.2 (331.2)	919.0 (416.9)	126.1 (57.2)	134.0 (60.8)	97.4 (44.2)	102.0 (46.3)	19.1 (8.6)	23.0 (10.4)	1,075.9 (488.0)	1,280.0 (580.6)

RIMS

5-PIECE

RIM SIZE DIA. - WIDTH / FLANGE HT.	RECOMMENDED TIRE SIZE(S)	COMPONENT WEIGHTS								AVG. ASSEMBLY WT. LBS (KG)	MAX. ASSEMBLY WT. LBS (KG)
		AVG. RIM BASE WT. LBS (KG)	MAX. RIM BASE WT. LBS (KG)	AVG. BEADSEAT BAND WT. LBS (KG)	MAX. BEADSEAT BAND WT. LBS (KG)	AVG. SIDE RING WT. [X2] LBS (KG)	MAX. SIDE RING WT. [X2] LBS (KG)	AVG. LOCK RING WT. LBS (KG)	MAX. LOCK RING WT. LBS (KG)		
35-31.00 / 4.0	37.25-35	625.9 (283.9)	- (-)	118.2 (53.6)	- (-)	128.4 (58.2)	- (-)	17.2 (7.8)	- (-)	1,018.1 (461.8)	- (-)
39-28.00 / 4.0	33.5-39	639.9 (290.3)	- (-)	132.6 (60.1)	- (-)	144.2 (65.4)	- (-)	19.4 (8.8)	- (-)	1,080.3 (490.0)	- (-)
39-32.00 / 4.0	40/65-39	723.0 (327.9)	- (-)	132.6 (60.1)	- (-)	144.2 (65.4)	- (-)	19.4 (8.8)	- (-)	1,163.4 (527.7)	- (-)
39-32.00 / 4.5	37.5R39	903.2 (409.7)	1,104.0 (500.8)	141.8 (64.3)	151.0 (68.5)	163.4 (74.1)	164.8 (74.8)	19.2 (8.7)	19.4 (8.8)	1,391.0 (630.9)	1,598.0 (724.8)
	41.25/70-39	929.7 (421.7)	1,156.9 (524.8)	149.3 (67.7)	165.9 (75.3)	180.8 (82.0)	196.8 (89.3)	21.1 (9.6)	22.8 (10.3)	1,373.9 (623.2)	1,563.7 (709.3)
45-36.00 / 4.5	45/65R45	1,417.2 (642.8)	1,767.0 (801.5)	168.7 (76.5)	188.0 (85.3)	249.8 (113.3)	384.0 (174.2)	36.2 (16.4)	78.0 (35.4)	2,096.6 (951.0)	2,801.0 (1,270.5)
49-17.00 / 3.5	24.00R49	615.1 (279.0)	690.0 (313.0)	169.1 (76.7)	173.0 (78.5)	174.5 (79.2)	175.0 (79.4)	28.9 (13.1)	29.8 (13.5)	1,160.7 (526.5)	1,241.0 (562.9)
49-17.00 / 4.0	24.00R49	1,748.0 (792.9)	- (-)	174.0 (78.9)	- (-)	182.0 (82.6)	- (-)	90.0 (40.8)	- (-)	2,376.0 (1,077.7)	- (-)
49-19.5 / 4.0	27.00R49	824.4 (374.0)	1,231.0 (558.4)	181.9 (82.5)	202.0 (91.6)	265.3 (120.3)	322.0 (146.1)	50.1 (22.7)	90.0 (40.8)	1,549.1 (702.7)	2,134.0 (968.0)
51-22.00 / 4.5	30.00R51	1,163.0 (527.5)	1,453.0 (659.1)	297.8 (135.1)	303.4 (137.6)	333.1 (151.1)	485.0 (220.0)	89.3 (40.5)	94.6 (42.9)	2,218.0 (1,006.1)	2,363.0 (1,071.8)
51-22.00 / 5.0	30.00R51	1,822.0 (826.4)	- (-)	344.0 (156.0)	- (-)	587.0 (266.3)	- (-)	84.0 (38.1)	- (-)	3,424.0 (1,553.1)	- (-)
51-24.00 / 5.0	33.00R51	1,276.8 (579.1)	1,545.6 (701.1)	320.2 (145.2)	363.6 (164.9)	440.4 (199.8)	587.0 (266.3)	97.5 (44.2)	114.0 (51.7)	2,572.2 (1,166.7)	2,933.0 (1,330.4)
51-26.00 / 5.0	36.00R51	1,349.4 (612.1)	1,733.0 (786.1)	309.4 (140.3)	344.0 (156.0)	442.5 (200.7)	587.0 (266.3)	89.3 (40.5)	94.6 (42.9)	2,633.0 (1,194.3)	3,335.0 (1,512.7)
51-32.00 / 4.5	37.5-51	1,436.6 (651.6)	- (-)	303.4 (137.6)	- (-)	245.2 (111.2)	- (-)	94.6 (42.9)	- (-)	2,325.0 (1,054.6)	- (-)

RIM SIZE DIA. - WIDTH / FLANGE HT.	RECOMMENDED TIRE SIZE(S)	COMPONENT WEIGHTS								AVG. ASSEMBLY WT. LBS (KG)	MAX. ASSEMBLY WT. LBS (KG)
		AVG. RIM BASE WT. LBS (KG)	MAX. RIM BASE WT. LBS (KG)	AVG. BEADSEAT BAND WT. LBS (KG)	MAX. BEADSEAT BAND WT. LBS (KG)	AVG. SIDE RING WT. [X2] LBS (KG)	MAX. SIDE RING WT. [X2] LBS (KG)	AVG. LOCK RING WT. LBS (KG)	MAX. LOCK RING WT. LBS (KG)		
51-40.00 / 4.5	50/65R51	1,927.3 (874.2)	2,465.0 (1,118.1)	371.5 (168.5)	476.4 (216.1)	397.8 (180.4)	518.0 (235.0)	97.5 (44.2)	114.0 (51.7)	2,992.9 (1,357.5)	3,490.0 (1,583.0)
	50.00-51	1,428.7 (648.0)	1,751.4 (794.4)	303.2 (137.5)	303.4 (137.6)	514.0 (233.1)	518.0 (235.0)	94.6 (42.9)	- (-)	2,854.5 (1,294.8)	3,169.0 (1,437.4)
51-40.00 / 5.0	50/65R51	2,611.0 (1,184.3)	- (-)	390.0 (176.9)	- (-)	587.0 (266.3)	- (-)	84.0 (38.1)	- (-)	4,259.0 (1,931.8)	- (-)
57-27.00 / 6.0	37.00-57	1,598.3 (725.0)	2,122.8 (962.9)	393.7 (178.6)	549.6 (249.3)	530.2 (240.5)	556.0 (252.2)	111.7 (50.7)	127.2 (57.7)	3,327.7 (1,509.4)	4,237.9 (1,922.3)
57-29.00 / 6.0	40.00R57	1,952.1 (885.5)	2,438.0 (1,105.9)	396.9 (180.0)	549.6 (249.3)	588.2 (266.8)	878.0 (398.3)	108.0 (49.0)	127.2 (57.7)	3,759.6 (1,705.3)	4,701.0 (2,132.3)
57-32.00 / 5.0	46/90R57	2,003.0 (908.5)	- (-)	410.0 (186.0)	- (-)	711.0 (322.5)	- (-)	97.0 (44.0)	- (-)	3,932.0 (1,783.5)	- (-)
57-32.00 / 6.0	46/90R57	1,809.0 (820.5)	- (-)	346.0 (156.9)	- (-)	556.0 (252.2)	- (-)	102.0 (46.3)	- (-)	3,369.0 (1,528.2)	- (-)
57-34.00 / 5.0	50/80R57	1,987.0 (901.3)	- (-)	346.0 (156.9)	- (-)	500.0 (226.8)	- (-)	102.0 (46.3)	- (-)	3,435.0 (1,558.1)	- (-)
57-36.00 / 6.0	52/80-57	2,713.0 (1,230.6)	- (-)	408.0 (185.1)	- (-)	556.0 (252.2)	- (-)	102.0 (46.3)	- (-)	4,335.0 (1,966.3)	- (-)
57-44.00 / 5.0	44.5/80R57	3,058.6 (1,387.4)	3,340.0 (1,515.0)	457.3 (207.4)	519.0 (235.4)	607.6 (275.6)	711.0 (322.5)	101.7 (46.1)	106.0 (48.1)	4,801.9 (2,178.1)	5,378.0 (2,439.4)
57-47.00 / 6.0	60/80R57	3,272.5 (1,484.4)	3,322.0 (1,506.8)	488.0 (221.4)	568.0 (257.6)	717.0 (325.2)	878.0 (398.3)	99.5 (45.1)	102.0 (46.3)	5,294.0 (2,401.3)	5,743.0 (2,605.0)
57-52.00 / 6.0	65/65R57	3,563.0 (1,616.1)	- (-)	408.0 (185.1)	- (-)	556.0 (252.2)	- (-)	102.0 (46.3)	- (-)	5,185.0 (2,351.9)	- (-)
57-60.00 / 6.0	70/70R57	3,828.0 (1,736.4)	- (-)	468.0 (212.3)	- (-)	503.0 (228.2)	- (-)	102.0 (46.3)	- (-)	5,404.0 (2,451.2)	- (-)
63-36.00 / 5.0	53/80R63	3,927.6 (1,781.5)	4,955.0 (2,247.6)	627.4 (284.6)	781.0 (354.3)	686.2 (311.3)	907.0 (411.4)	110.0 (49.9)	116.0 (52.6)	6,039.8 (2,739.6)	6,570.0 (2,980.1)
63-37.00 / 5.0	55/80R63	4,180.0 (1,896.0)	- (-)	473.0 (214.5)	- (-)	907.0 (411.4)	- (-)	105.0 (47.6)	- (-)	6,572.0 (2,981.0)	- (-)

RIMS

5-PIECE

RIM SIZE DIA. - WIDTH / FLANGE HT.	RECOMMENDED TIRE SIZE(S)	COMPONENT WEIGHTS								AVG. ASSEMBLY WT. LBS (KG)	MAX. ASSEMBLY WT. LBS (KG)
		AVG. RIM BASE WT. LBS (KG)	MAX. RIM BASE WT. LBS (KG)	AVG. BEADSEAT BAND WT. LBS (KG)	MAX. BEADSEAT BAND WT. LBS (KG)	AVG. SIDE RING WT. [X2] LBS (KG)	MAX. SIDE RING WT. [X2] LBS (KG)	AVG. LOCK RING WT. LBS (KG)	MAX. LOCK RING WT. LBS (KG)		
63-38.00 / 5.0	56/80R63	4,246.0 (1,926.0)	- (-)	473.0 (214.5)	- (-)	907.0 (411.4)	- (-)	105.0 (47.6)	- (-)	6,638.0 (3,010.9)	- (-)
63-41.00 / 5.0	55/80R63	3,823.7 (1,734.4)	4,103.0 (1,861.1)	661.7 (300.1)	781.0 (354.3)	745.3 (338.1)	836.0 (379.2)	116.0 (52.6)	- (-)	6,092.0 (2,763.3)	6,593.0 (2,990.5)
	58/80R63	4,586.5 (2,080.4)	5,205.0 (2,360.9)	578.0 (262.2)	683.0 (309.8)	597.5 (271.0)	907.0 (411.4)	107.5 (48.8)	109.0 (49.4)	6,467.0 (2,933.4)	6,573.0 (2,981.5)
	56/80R63	4,284.7 (1,943.5)	- (-)	741.3 (336.2)	- (-)	743.1 (337.1)	- (-)	140.9 (63.9)	- (-)	5,754.3 (2,610.1)	- (-)
63-44.00 / 5.0	58/80R63	4,026.7 (1,826.5)	4,125.0 (1,871.1)	661.7 (300.1)	781.0 (354.3)	745.3 (338.1)	836.0 (379.2)	116.0 (52.6)	- (-)	6,295.0 (2,855.4)	6,615.0 (3,000.5)
	59/80R63	4,601.8 (2,087.3)	5,534.0 (2,510.2)	664.3 (301.3)	781.0 (354.3)	716.4 (325.0)	907.0 (411.4)	116.4 (52.8)	140.9 (63.9)	6,815.6 (3,091.5)	6,951.0 (3,152.9)

RIM SIZE DIA. - WIDTH / FLANGE HT. (6 OR 7 PIECE ASSEMBLY)	RECOMMENDED TIRE SIZE(S)	COMPONENT WEIGHTS								AVG. ASSEMBLY WT. LBS (KG)	MAX. ASSEMBLY WT. LBS (KG)
		AVG. RIM BASE WT. LBS (KG)	MAX. RIM BASE WT. LBS (KG)	AVG. BEADSEAT BAND WT. [X2] LBS (KG)	MAX. BEADSEAT BAND WT. [X2] LBS (KG)	AVG. SIDE RING WT. [X2] LBS (KG)	MAX. SIDE RING WT. [X2] LBS (KG)	AVG. LOCK RING WT. [X2 IF 7PC] LBS (KG)	MAX. LOCK RING WT. [X2 IF 7PC] LBS (KG)		
25-25.00 / 3.5 (6 PIECE)	29.5R25	482.0 (218.6)	- (-)	90.0 (40.8)	- (-)	132.0 (59.9)	- (-)	12.0 (5.4)	- (-)	938.0 (425.5)	- (-)
29-25.00 / 3.5 (6 PIECE)	29.5R29	655.0 (297.1)	- (-)	92.0 (41.7)	- (-)	144.0 (65.3)	- (-)	16.0 (7.3)	- (-)	1,143.0 (518.5)	- (-)
29-27.00 / 3.5 (6 PIECE)	33.25R29	601.0 (272.6)	- (-)	92.0 (41.7)	- (-)	144.0 (65.3)	- (-)	14.0 (6.4)	- (-)	1,087.0 (493.1)	- (-)
33-28.00 / 3.5 (6 PIECE)	35/65R33	778.0 (352.9)	866.0 (392.8)	133.0 (60.3)	145.0 (65.8)	148.0 (67.1)	- (-)	19.5 (8.8)	21.0 (9.5)	1,359.5 (616.7)	1,473.0 (668.1)
35-15.00 / 3.0 (6 PIECE)	21.00R35	513.0 (232.7)	- (-)	102.0 (46.3)	- (-)	76.0 (34.5)	- (-)	23.0 (10.4)	- (-)	892.0 (404.6)	- (-)
35-15.00 / 3.0 (7 PIECE)	21.00R35	486.0 (220.4)	- (-)	102.0 (46.3)	- (-)	76.0 (34.5)	- (-)	23.0 (10.4)	- (-)	888.0 (402.8)	- (-)
35-17.00 / 3.5 (6 PIECE)	24.00R35	528.0 (239.5)	- (-)	126.0 (57.2)	- (-)	194.0 (88.0)	- (-)	23.0 (10.4)	- (-)	1,191.0 (540.2)	- (-)
35-17.00 / 3.5 (7 PIECE)	24.00R35	547.3 (248.2)	580.5 (263.3)	118.2 (53.6)	126.0 (57.2)	168.4 (76.4)	194.0 (88.0)	24.1 (10.9)	25.2 (11.4)	1,073.6 (487.0)	1,200.0 (544.3)
45-36.00 / 4.5 (6 PIECE)	45/65R45	1,851.0 (839.6)	- (-)	188.0 (85.3)	- (-)	384.0 (174.2)	- (-)	78.0 (35.4)	- (-)	3,073.0 (1,393.9)	- (-)
49-19.50 / 4.0 (6 PIECE)	27.00R49	1,294.0 (586.9)	- (-)	174.0 (78.9)	- (-)	322.0 (146.1)	- (-)	83.0 (37.6)	- (-)	2,369.0 (1,074.6)	- (-)
49-19.50 / 4.0 (7 PIECE)	27.00R49	932.4 (422.9)	1,253.0 (568.4)	204.5 (92.8)	264.0 (119.7)	234.4 (106.3)	322.0 (146.1)	51.0 (23.1)	85.0 (38.6)	1,837.5 (833.5)	2,413.0 (1,094.5)
51-24.00 / 5.0 (6 PIECE)	33.00R51	1,341.0 (608.3)	1,365.0 (619.2)	316.0 (143.3)	344.0 (156.0)	450.0 (204.1)	587.0 (266.3)	84.5 (38.3)	85.0 (38.6)	2,957.5 (1,341.5)	3,312.0 (1,502.3)
51-24.00 / 5.0 (7 PIECE)	33.00R51	1,513.0 (686.3)	1,828.9 (829.6)	388.0 (176.0)	432.0 (196.0)	475.3 (215.6)	587.0 (266.3)	99.0 (44.9)	114.0 (51.7)	3,182.8 (1,443.7)	3,228.0 (1,464.2)
51-26.00 / 5.0 (6 PIECE)	36.00R51	1,396.0 (633.2)	1,419.0 (643.6)	316.0 (143.3)	344.0 (156.0)	450.0 (204.1)	587.0 (266.3)	84.5 (38.3)	85.0 (38.6)	3,012.5 (1,366.4)	3,366.0 (1,526.8)
51-26.00 / 5.0 (7 PIECE)	36.00R51	1,248.0 (566.1)	- (-)	344.0 (156.0)	- (-)	587.0 (266.3)	- (-)	84.0 (38.1)	- (-)	3,279.0 (1,487.3)	- (-)

RIMS

6-PIECE

RIM SIZE DIA. - WIDTH / FLANGE HT. (6 OR 7 PIECE ASSEMBLY)	RECOMMENDED TIRE SIZE(S)	COMPONENT WEIGHTS								AVG. ASSEMBLY WT. LBS (KG)	MAX. ASSEMBLY WT. LBS (KG)
		AVG. RIM BASE WT. LBS (KG)	MAX. RIM BASE WT. LBS (KG)	AVG. BEADSEAT BAND WT. [X2] LBS (KG)	MAX. BEADSEAT BAND WT. [X2] LBS (KG)	AVG. SIDE RING WT. [X2] LBS (KG)	MAX. SIDE RING WT. [X2] LBS (KG)	AVG. LOCK RING WT. [X2 IF 7PC] LBS (KG)	MAX. LOCK RING WT. [X2 IF 7PC] LBS (KG)		
57-27.00 / 6.0 (6 PIECE)	37.00R57	1,453.0 (659.1)	- (-)	410.0 (186.0)	- (-)	878.0 (398.3)	- (-)	96.0 (43.5)	- (-)	4,125.0 (1,871.1)	- (-)
57-27.00 / 6.0 (7 PIECE)	37.00R57	1,960.7 (889.3)	2,511.3 (1,139.1)	475.0 (215.5)	540.0 (244.9)	713.8 (323.8)	878.0 (398.3)	112.1 (50.8)	127.2 (57.7)	4,789.3 (2,172.4)	5,399.5 (2,449.2)
57-29.00 / 6.0 (6 PIECE)	40.00R57	1,655.0 (750.7)	1,781.0 (807.8)	378.0 (171.5)	410.0 (186.0)	717.0 (325.2)	878.0 (398.3)	100.0 (45.4)	104.0 (47.2)	3,945.0 (1,789.4)	4,201.0 (1,905.5)
57-29.00 / 6.0 (7 PIECE)	40.00R57	2,166.4 (982.6)	2,583.9 (1,172.0)	475.0 (215.5)	540.0 (244.9)	713.8 (323.8)	878.0 (398.3)	112.1 (50.8)	127.2 (57.7)	4,478.7 (2,031.5)	5,472.1 (2,482.1)
57-32.00 / 6.0 (6 PIECE)	46/90R57	1,837.0 (833.2)	1,845.0 (836.9)	378.0 (171.5)	410.0 (186.0)	717.0 (325.2)	878.0 (398.3)	99.0 (44.9)	102.0 (46.3)	4,126.0 (1,871.5)	4,517.0 (2,048.9)
57-32.00 / 6.0 (7 PIECE)	46/90R57	1,781.0 (807.8)	- (-)	410.0 (186.0)	- (-)	878.0 (398.3)	- (-)	97.0 (44.0)	- (-)	4,550.0 (2,063.8)	- (-)
57-34.00 / 6.0 (6 PIECE)	50/90R57	1,950.0 (884.5)	- (-)	410.0 (186.0)	- (-)	878.0 (398.3)	- (-)	97.0 (44.0)	- (-)	4,623.0 (2,097.0)	- (-)
57-34.00 / 6.5 (7 PIECE)	50/90R57	1,868.0 (847.3)	- (-)	410.0 (186.0)	- (-)	1,070.0 (485.3)	- (-)	97.0 (44.0)	- (-)	5,021.0 (2,277.5)	- (-)
57-44.00 / 6.5 (6 PIECE)	44.5/80R57	3,209.0 (1,455.6)	- (-)	519.0 (235.4)	- (-)	1,070.0 (485.3)	- (-)	97.0 (44.0)	- (-)	6,484.0 (2,941.1)	- (-)
57-47.00 / 6.5 (6 PIECE)	60/80R57	3,338.0 (1,514.1)	- (-)	519.0 (235.4)	- (-)	1,070.0 (485.3)	- (-)	97.0 (44.0)	- (-)	6,613.0 (2,999.6)	- (-)
63-36.00 / 5.0 (6 PIECE)	53/80R63	4,148.5 (1,881.7)	4,721.0 (2,141.4)	578.0 (262.2)	683.0 (309.8)	597.5 (271.0)	907.0 (411.4)	107.0 (48.5)	108.0 (49.0)	6,606.5 (2,996.7)	6,771.0 (3,071.3)
63-36.00 / 5.0 (7 PIECE)	53/80R63	4,627.0 (2,098.8)	5,206.0 (2,361.4)	578.0 (262.2)	683.0 (309.8)	597.5 (271.0)	907.0 (411.4)	106.5 (48.3)	108.0 (49.0)	7,192.5 (3,262.5)	7,366.0 (3,341.2)
63-38.00 / 5.0 (6 PIECE)	56/80R63	3,957.0 (1,794.9)	- (-)	473.0 (214.5)	- (-)	907.0 (411.4)	- (-)	106.0 (48.1)	- (-)	6,823.0 (3,094.9)	- (-)
63-38.00 / 5.0 (7 PIECE)	56/80R63	4,116.0 (1,867.0)	- (-)	473.0 (214.5)	- (-)	907.0 (411.4)	- (-)	105.0 (47.6)	- (-)	7,087.0 (3,214.6)	- (-)
63-41.00 / 5.0 (6 PIECE)	58/80R63	4,453.0 (2,019.8)	4,928.0 (2,235.3)	578.0 (262.2)	683.0 (309.8)	597.5 (271.0)	907.0 (411.4)	108.0 (49.0)	110.0 (49.9)	6,912.0 (3,135.2)	6,980.0 (3,166.1)

RIMS

6-PIECE

RIM SIZE DIA. - WIDTH / FLANGE HT. (6 OR 7 PIECE ASSEMBLY)	RECOMMENDED TIRE SIZE(S)	COMPONENT WEIGHTS								AVG. ASSEMBLY WT. LBS (KG)	MAX. ASSEMBLY WT. LBS (KG)
		AVG. RIM BASE WT. LBS (KG)	MAX. RIM BASE WT. LBS (KG)	AVG. BEADSEAT BAND WT. [X2] LBS (KG)	MAX. BEADSEAT BAND WT. [X2] LBS (KG)	AVG. SIDE RING WT. [X2] LBS (KG)	MAX. SIDE RING WT. [X2] LBS (KG)	AVG. LOCK RING WT. [X2 IF 7PC] LBS (KG)	MAX. LOCK RING WT. [X2 IF 7PC] LBS (KG)		
63-41.00 / 5.0 (7 PIECE)	58/80R63	4,909.0 (2,226.7)	5,754.0 (2,610.0)	578.0 (262.2)	683.0 (309.8)	597.5 (271.0)	907.0 (411.4)	106.5 (48.3)	108.0 (49.0)	7,474.5 (3,390.4)	7,914.0 (3,589.7)
63-44.00 / 5.0 (6 PIECE)	59/80R63	4,083.0 (1,852.0)	- (-)	473.0 (214.5)	- (-)	907.0 (411.4)	- (-)	106.0 (48.1)	- (-)	6,949.0 (3,152.0)	- (-)
63-44.00 / 5.0 (7 PIECE)	59/80R63	4,509.7 (2,045.5)	4,903.3 (2,224.1)	608.1 (275.8)	743.1 (337.1)	824.2 (373.8)	907.0 (411.4)	123.0 (55.8)	140.9 (63.9)	7,674.0 (3,480.8)	8,260.9 (3,747.1)